Solution NRJ

TECHNICAL SHEET

Perkins 100 kW



Perkins 100 kW diesel generator

Enclosed, sound-attenuated generator set for residential and commercial backup or job sites.

$44,000 CAD

before taxes

SPECIFICATIONS

Engine	Perkins 1104D-E44TAG2, 4 cylinders, turbocharged	**Fuel tank**	600 litres
Output	100 kW · 100 kVA	**Block heater**	Included
Voltage	120/240 V · Single-phase · 60 Hz	**Dimensions (L × W)**	102 × 43 in (259 × 109 cm)
Also available in	120/208 V, 277/480 V and 347/600 V three-phase, same price	**Battery charger**	Smart, included
Power factor	1.0	**Controller**	Deep Sea DSE6120
Alternator	Genuine Stamford	**Certifications**	CSA · EPA Tier 3
Enclosure	Sound-attenuated		

TECHNICAL DATA AND EQUIPMENT

PERKINS ENGINE 1104D-E44TAG2

Cylinders	4 inline, 4-stroke
Aspiration	Turbo, air-to-air charge cooled
Displacement	4.4 L
Bore × stroke	105 × 127 mm
Compression ratio	16.7:1
Speed	1,800 rpm
Speed governor	Electronic (ECM), droop ≤ 1%
Cooling	Liquid
Oil (total capacity)	8.4 L
Fuel use at full load	About 28 L/h
Starting	Electric 12 V DC

STAMFORD ALTERNATOR

Model	Stamford UCI274C, CSA approved
Excitation	Brushless, self-excited, single bearing
Voltage regulation	± 1% (no load to full load)
Insulation class	H
Protection rating	IP23

DSE6120 CONTROL PANEL

- Automatic start on utility power failure
- Display: voltage, frequency, engine speed, battery, running hours
- Automatic shutdown: low oil pressure, high temperature, overspeed, failure after 3 start attempts
- Schneider main breaker · ground fault relay
- Panel lighting, timer and LCD screen
- Low fuel level alarm

CONSTRUCTION

- Built-in containment base: oil or coolant leaks are collected, with no spill
- Large doors, quick-release handles, key lock
- Single-side servicing; opening front panel to clean the radiator
- Industrial silencer and flexible exhaust hose

INCLUDED

- Block heater and glow plugs
- Smart battery charger
- Prepared (oil, Prestone) and load-bank tested 2 h, 10% to 110%

MAINTENANCE

- Break-in: 60 h · oil: 250 h · fuel filter: 500 h
- Perkins filter numbers: generatricediesel.com/en-ca/technical-support/

Factory tested at 50, 75, 100 and 110% load · designed to ISO 8528, NEC and CEC. Warranty of 1 year or 1,500 hours, whichever comes first. Quotation: 438-350-6979 or ventes@solutionnrj.com. Product page and photos online.

Solution NRJ (9547-0233 Québec inc.) · 1380 Grande Allée, Unit 14, Terrebonne, Quebec J6W 4M3
438-350-6979 · ventes@solutionnrj.com · generatricediesel.com