Solution NRJ

TECHNICAL SHEET

Perkins 150 kW



Perkins 150 kW diesel generator

Enclosed, sound-attenuated generator set for residential and commercial backup or job sites.

$49,000 CAD

before taxes

SPECIFICATIONS

Engine	Perkins 1106D-E70TAG3, 6 cylinders, turbocharged	**Fuel tank**	600 litres
Output	150 kW · 187.5 kVA	**Block heater**	Included
Voltage	347/600 V · Three-phase · 60 Hz	**Dimensions (L × W)**	125.98 × 44.49 in (320 × 113 cm)
Also available in	120/240 V single-phase, 120/208 V and 277/480 V three-phase, same price	**Battery charger**	Smart, included
Power factor	0.8	**Controller**	Deep Sea DSE6120
Alternator	Genuine Stamford	**Certifications**	CSA · EPA Tier 3
Enclosure	Sound-attenuated		

TECHNICAL DATA AND EQUIPMENT

PERKINS ENGINE 1106D-E70TAG3

Cylinders	6 inline, 4-stroke
Aspiration	Turbocharged, aftercooled
Displacement	7.0 L
Bore × stroke	105 × 135 mm
Compression ratio	16.8:1
Speed	1,800 rpm
Speed governor	Electronic (ECM), droop ≤ 1%
Cooling	Liquid
Fuel use at full load	About 38 L/h
Starting	Electric 12 V DC

STAMFORD ALTERNATOR

Model	Stamford UCI274E, CSA approved
Excitation	Brushless, self-excited, single bearing
Voltage regulation	± 1% (no load to full load)
Insulation class	H
Protection rating	IP23

DSE6120 CONTROL PANEL

- Automatic start on utility power failure
- Display: voltage, frequency, engine speed, battery, running hours
- Automatic shutdown: low oil pressure, high temperature, overspeed, failure after 3 start attempts
- Schneider main breaker · ground fault relay
- Panel lighting, timer and LCD screen
- Low fuel level alarm

CONSTRUCTION

- Built-in containment base: oil or coolant leaks are collected, with no spill
- Large doors, quick-release handles, key lock
- Single-side servicing; opening front panel to clean the radiator
- Industrial silencer and flexible exhaust hose

INCLUDED

- Block heater and glow plugs
- Smart battery charger
- Prepared (oil, Prestone) and load-bank tested 2 h, 10% to 110%

MAINTENANCE

- Break-in: 60 h · oil: 250 h · fuel filter: 500 h
- Perkins filter numbers: generatricediesel.com/en-ca/technical-support/

Factory tested at 50, 75, 100 and 110% load · designed to ISO 8528, NEC and CEC. Warranty of 1 year or 1,500 hours, whichever comes first. Quotation: 438-350-6979 or ventes@solutionnrj.com. Product page and photos online.